



EJOT® self-drilling screw JT2-D-6-5.5/6.3 EJOGUARD



Length [mm]	 [mm]		Price/100 [EUR]	Order description	Article number	EAN
Sealing washer E19, Ø 19 mm						
62	35 - 48	250		JT2-D-6-5.5/6.3x62-E19 EJOGUARD	3 563 412 674	-
82	24 - 68	200		JT2-D-6-5.5/6.3x82-E19 EJOGUARD	3 563 612 674	-
102	44 - 88	200		JT2-D-6-5.5/6.3x102-E19 EJOGUARD	3 563 812 674	-
122	64 - 108	150		JT2-D-6-5.5/6.3x122-E19 EJOGUARD	3 567 012 674	-
152	94 - 138	100		JT2-D-6-5.5/6.3x152-E19 EJOGUARD	3 565 912 674	-
172	114 - 158	100		JT2-D-6-5.5/6.3x172-E19 EJOGUARD	3 566 412 674	-
192	134 - 178	100		JT2-D-6-5.5/6.3x192-E19 EJOGUARD	3 566 612 674	-
212	154 - 198	100		JT2-D-6-5.5/6.3x212-E19 EJOGUARD	3 566 712 674	-
232	174 - 218	100		JT2-D-6-5.5/6.3x232-E19 EJOGUARD	3 566 812 674	-
262	204 - 248	100		JT2-D-6-5.5/6.3x262-E19 EJOGUARD	3 566 912 674	-
Order information: Other sealing washer combinations upon request						

Application range

- Fastening sandwich panels to 1.5–5 mm steel substructure

Characteristics

- Case-hardened steel
- EJOGUARD corrosion protection
- Stainless steel sealing washer
- Pre-assembled sealing washer
- High thread

Technical Specifications

Diameter	5.5 mm
Drilling capacity $t_1 + t_2$	6.5 mm
Drive	Hexagon A/F8
Ø high thread	6.3 mm
Installation rotation speed	max. 1300 rpm

