

HIT-1

Safety information for 2-Component-products

Issue date: 25/01/2022

Revision date: 25/01/2022

Supersedes: 10/08/2017

Version: 1.1

SECTION 1: Kit identification

1.1 Product identifier

Product name Product code HIT-1 BU Anchor

1.2 Details of the supplier of the Safety information for 2-Component-products

Hilti, Inc. Legacy Tower, Suite 1000 7250 Dallas Parkway TX 75024 Plano - USA T +1 9724035800 1-800-879-8000 toll free - F +1 918 254 0522

SECTION 2: General information

Storage

Storage temperature : 5 - 25 °C

A SDS for each of these components is included. Please do not separate any component SDS from this cover page

This Kit should be handled in accordance with good laboratory practices and appropriate personal protective equipment should be used

SECTION 3: Kit contents

Classification of the Product

GHS-US classification

Eye Irrit. 2H319 - Causes serious eye irritation.Skin Sens. 1H317 - May cause an allergic skin reaction.

Label elements

GHS US labelling

Hazard pictograms (GHS US)

Signal word (GHS US) Hazardous ingredients Hazard statements (GHS US)

Precautionary statements (GHS US)



▼	
GHS07	
Warning	
methacrylates, dibenzoyl peroxide	
May cause an allergic skin reaction. Causes serious eye irritation.	
Wear eye protection, protective clothing, protective gloves. Do not get in eyes, on skin, or on clothing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. If on skin: Wash with plenty of water.	



HIT-1 Safety information for 2-Component-products

Additional information

Plastic-cartridge, contains: Methacrylate resin, inorganic filler Dibenzoyl peroxide, phlegmatized

Name	General description	Quantity	Unit	GHS-US classification
HIT-1, A		1	pcs (pieces)	Eye Irrit. 2, H319 Skin Sens. 1, H317
НІТ-1, В		1	pcs (pieces)	Eye Irrit. 2A, H319 Skin Sens. 1, H317

SECTION 4: General advice

General advice

For professional users only

SECTION 5: Safe handling advice

General measures	Spilled material may present a slipping hazard
Environmental precautions	Prevent entry to sewers and public waters Notify authorities if liquid enters sewers or public waters
Storage conditions	Keep cool. Protect from sunlight.
Precautions for safe handling	Wear personal protective equipment Avoid contact with skin and eyes Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work Provide good ventilation in process area to prevent formation of vapour
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation Mechanically recover the product Store away from other materials.
For containment	Collect spillage.
Incompatible materials	Sources of ignition Direct sunlight
Incompatible products	Strong bases Strong acids

SECTION 6: First aid measures

First-aid measures after eye contact	Rinse immediately with plenty of water Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists
First-aid measures after ingestion	Rinse mouth Get medical advice/attention. Do not induce vomiting Obtain emergency medical attention
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air Allow the victim to rest
First-aid measures after skin contact	Wash contaminated clothing before reuse. Wash with plenty of water/ If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures general	Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person If you feel unwell, seek medical advice (show the label where possible)



HIT-1 Safety information for 2-Component-products

Symptoms/effects after eye contact Symptoms/effects after skin contact Other medical advice or treatment	May cause severe irritation May cause an allergic skin reaction. Treat symptomatically
SECTION 7: Fire fighting measures	
Firefighting instructions	Use water spray or fog for cooling exposed containers Exercise caution when fighting any chemical fire Prevent fire fighting water from entering the environment
Protection during firefighting	Self-contained breathing apparatus Do not enter fire area without proper protective equipment, including respiratory protection
Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide Carbon monoxide

SECTION 8: Other information

No data available



according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 01/21/2022 Revision date: 01/21/2022 Supersedes: 08/10/2017 Version: 1.1

SECTION 1: Identification	
1.1. Identification	
Product form	Mixture
Product name	HIT-1, B
Product code	BU Anchor
1.2. Recommended use and restriction	ns on use
Use of the substance/mixture	Composite mortar component for fasteners in the construction industry
Recommended use	For professional use only
1.3. Supplier	
Supplier Hilti, Inc. Legacy Tower, Suite 1000 7250 Dallas Parkway Plano, TX 75024 - USA T +1 9724035800 1-800-879-8000 toll free - F +1 918 254 0522	Department issuing data specification sheet Hilti Entwicklungsgesellschaft mbH Hiltistraße 6 Kaufering, 86916 - Deutschland T +49 8191 906876 anchor.hse@hilti.com
1.4. Emergency telephone number	
Emergency number	Chem-Trec Tel.: 1 800 424 9300 (USA, PR, Virgin Islands, Canada) Tel.: 703 527 3887 (Other countries) +1 918 8723000 1-800-879-8000 toll free

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Serious eye damage/eye irritation, Category 2A Skin sensitisation, Category 1 Full text of H-statements: see section 16 H319 H317 Causes serious eye irritation. May cause an allergic skin reaction.

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US)

Signal word (GHS US) Hazard statements (GHS US)

Precautionary statements (GHS US)



H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation.	
P280 - Wear eye protection, protective clothing, protective gloves.	
P262 - Do not get in eyes, on skin, or on clothing.	
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several min	utes. Remove
contact lenses, if present and easy to do. Continue rinsing.	
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.	
P337+P313 - If eye irritation persists: Get medical advice/attention.	
P302+P352 - If on skin: Wash with plenty of water.	

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. **Substances**

Not applicable

3.2.

Mixtures % Name **Product identifier GHS-US** classification Quartz (SiO2) (CAS-No.) 14808-60-7 40 - 60 Carc. 1A, H350 Org. Perox. B, H241 dibenzoyl peroxide (CAS-No.) 94-36-0 1 - 15

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. **Description of first aid measures**

First-aid measures general	Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	Wash contaminated clothing before reuse. Wash with plenty of water/ If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.

4.2.	Most important symptoms and	effects (acute and delayed)
	al adverse human health effects and	No additional information available.
sympto		

Symptoms/effects after skin contact	May cause an allergic skin reaction.
Symptoms/effects after eye contact	May cause severe irritation.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extingui	Suitable (and unsuitable) extinguishing media	
Suitable extinguishing media	Water spray. Carbon dioxide. Dry powder. Foam. Sand.	
Unsuitable extinguishing media	Do not use a heavy water stream.	
5.2. Specific hazards arising from the chemical		
I have a device of the second sector in the second sector in the second sector is the second sector in the second sector is the second	The second decomposition and sectors a Combined distribution of the second se	

Hazardous decomposition products in case of	Thermal decomposition generates : Carbon dioxide. Carbon monoxide.
fire	

Eye Irrit. 2A, H319 Skin Sens. 1, H317

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructionsUse water spray or fog for cooling exposed containers. Exercise caution when fighting any
chemical fire. Prevent fire fighting water from entering the environment.Protection during firefightingSelf-contained breathing apparatus. Do not enter fire area without proper protective equipment,
including respiratory protection.

SECTION 6: Accidental release measures

6.1.	Personal precautions, protective equipment and emergency procedures		
General measures		Spilled material may present a slipping hazard.	
6.1.1.	6.1.1. For non-emergency personnel		
Emergency procedures		Evacuate unnecessary personnel.	
6.1.2.	For emergency responders		
Protective equipment		Use personal protective equipment as required. Equip cleanup crew with proper protection.	
Emergency procedures		Ventilate area.	

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods	Methods and material for containment and cleaning up	
For containment	Collect spillage.	
Methods for cleaning	up This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. Store away from other materials.	
Other information	Dispose of materials or solid residues at an authorized site.	

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe har	ndling
Precautions for safe handling	Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.
Hygiene measures	Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.
7.2. Conditions for safe stor	age, including any incompatibilities
Storage conditions	Keep cool. Protect from sunlight.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Storage temperature	5 – 25 °C
Heat and ignition sources	Keep away from heat and direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

HIT-1, B		
USA - ACGIH - Occupational Exposure Limits		
Local name	Benzoyl peroxide	

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ACGIH OEL TWA	5 mg/m³	
Remark (ACGIH)	TLV® Basis: URT & skin irr. Notations: A4 (Not classifiable as a Human Carcinogen)	
Regulatory reference	ACGIH 2021	
USA - OSHA - Occupational Exposure I	Limits	
Local name	Benzoyl peroxide	
OSHA PEL TWA [1]	5 mg/m³	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	
dibenzoyl peroxide (94-36-0)		
USA - ACGIH - Occupational Exposure	Limits	
Local name	Benzoyl peroxide	
ACGIH OEL TWA	5 mg/m³	
Remark (ACGIH)	TLV® Basis: URT & skin irr. Notations: A4 (Not classifiable as a Human Carcinogen)	
Regulatory reference	ACGIH 2020	
USA - OSHA - Occupational Exposure I	Limits	
Local name	Benzoyl peroxide	
OSHA PEL TWA [1]	5 mg/m ³	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	
Quartz (SiO2) (14808-60-7)		
USA - ACGIH - Occupational Exposure	Limits	
Local name	Silica crystaline - quartz	
ACGIH OEL TWA	0.025 mg/m ³ (Respirable fraction)	
Remark (ACGIH)	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)	
Regulatory reference	ACGIH 2022	
USA - OSHA - Occupational Exposure I	Limits	
Local name	Silica, crystalline quartz, respirable dust	
Remark (OSHA)	(3) See Table Z-3.	
Additional information	The product has a pasty consistency. Exposure limit values for respirable dusts are not relevan for this product.	
8.2. Appropriate engineering co	ontrols	

Appropriate engineering controls	Ensure adequate ventilation.
Environmental exposure controls	Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Safety glasses. Gloves. Protective clothing. Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Туре	Material	Permeation	Thickness (mm)	Penetration
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0,12	

Eye protection:

Wear security glasses which protect from splashes

Туре	Field of application	Characteristics
Safety glasses	Droplet	clear

Skin and body protection:

Wear suitable protective clothing

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

3.1. Information on basic physical and chemical properties		
Physical state	Solid	
Appearance	Thixotropic paste.	
Colour	Black	
Odour	There may be no odour warning properties, odour is subjective and inadequate to warn of	
	overexposure.	
	Mixture contains one or more component(s) which have the following odour: Odourless	
Odour threshold	No data available	
pH	No data available	
Melting point	No data available	
Freezing point	No data available	
Boiling point	No data available	
Flash point	No data available	
Relative evaporation rate (butylacetate=1)	No data available	
Flammability (solid, gas)	No data available	
Vapour pressure	No data available	
Relative vapour density at 20 °C	No data available	
Relative density	No data available	
Density	1.59 g/cm ³	
Solubility	No data available	
Partition coefficient n-octanol/water (Log Pow)	No data available	
Auto-ignition temperature	No data available	
Decomposition temperature	No data available	
Viscosity, kinematic	No data available	
Viscosity, dynamic	No data available	
Explosive limits	No data available	
Explosive properties	No data available	
Oxidising properties	No data available	

9.2. Other information

VOC content

4.3 % (DIN EN ISO 11890-2)

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects			
Acute toxicity (oral)	Not classified		
Acute toxicity (dermal)	Not classified		
Acute toxicity (inhalation)	Not classified		
Skin corrosion/irritation	Not classified		
Serious eye damage/irritation	Causes serious eye irritation.		
Respiratory or skin sensitisation	May cause an allergic skin reaction.		
Germ cell mutagenicity	Not classified		
Carcinogenicity	Not classified		
dibenzoyl peroxide (94-36-0)			
IARC group	3 - Not classifiable		
Quartz (SiO2) (14808-60-7)	Quartz (SiO2) (14808-60-7)		
IARC group	1 - Carcinogenic to humans		
Reproductive toxicity	Not classified		
STOT-single exposure	Not classified		
STOT-repeated exposure	Not classified		
Aspiration hazard Viscosity, kinematic	Not classified		
Potential adverse human health effects and	No additional information available.		

symptoms	
Symptoms/effects after skin contact	May cause an allergic skin reaction.
Symptoms/effects after eye contact	May cause severe irritation.

SECTION 12: Ecological information

12.1. Toxicity

dibenzoyl peroxide (94-36-0)		
EC50 - Crustacea [1]	0.11 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)	
LC50 - Fish [2]	0.0602 mg/l (96h; Oncorhynchus mykiss; ECHA)	
ErC50 algae	0.0711 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)	
NOEC (acute)	0.0316 mg/l (96h; Oncorhynchus mykiss; ECHA)	
NOEC chronic fish	0.001 mg/l	

12.2. Persistence and degradability

dibenzoyl peroxide (94-36-0)	
Persistence and degradability	Readily biodegradable in water. Not established. May cause long-term adverse effects in the environment.

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Quartz (SiO2) (14808-60-7)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

12.3. Bioaccumulative potential

dibenzoyl peroxide (94-36-0)	
Partition coefficient n-octanol/water (Log Pow)	3.71
Bioaccumulative potential Low bioaccumulation potential (Log Kow < 4).	
Quartz (SiO2) (14808-60-7)	
Bioaccumulative potential	No bioaccumulation data available.

12.4. Mobility in soil

dibenzoyl peroxide (94-36-0)	
Surface tension	No data available (test not performed)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
Ecology - soil	Low potential for mobility in soil.
Quartz (SiO2) (14808-60-7)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for mobility in soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations		
13.1. Disposal methods		
Regional legislation (waste)	Disposal must be done according to official regulations.	
Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.	
Ecology - waste materials	Avoid release to the environment.	

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	ΙΑΤΑ	RID
14.1. UN number			
UN 3077	UN 3077	UN 3077	UN 3077
14.2. UN proper shipping nar	ne		
ENVIRONMENTALLY	ENVIRONMENTALLY	Environmentally hazardous	ENVIRONMENTALLY
HAZARDOUS SUBSTANCE,	HAZARDOUS SUBSTANCE,	substance, solid, n.o.s. (dibenzoyl	HAZARDOUS SUBSTANCE,
SOLID, N.O.S. (dibenzoyl	SOLID, N.O.S. (dibenzoyl	peroxide)	SOLID, N.O.S. (dibenzoyl
peroxide)	peroxide)		peroxide)

HIT-1, B

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ADR	IMDG	ΙΑΤΑ	RID
Transport document description			
UN 3077 ENVIRONMENTALLY	UN 3077 ENVIRONMENTALLY	UN 3077 Environmentally	UN 3077 ENVIRONMENTALLY
HAZARDOUS SUBSTANCE,	HAZARDOUS SUBSTANCE,	hazardous substance, solid,	HAZARDOUS SUBSTANCE,
SOLID, N.O.S. (dibenzoyl	SOLID, N.O.S. (dibenzoyl	n.o.s. (dibenzoyl peroxide), 9, III	SOLID, N.O.S. (dibenzoyl
peroxide), 9, III, (-)	peroxide), 9, III, MARINE		peroxide), 9, III
	POLLUTANT		
14.3. Transport hazard class(es)		
9	9	9	9
14.4. Packing group			
III			111
14.5. Environmental hazards			
Dangerous for the environment:	Dangerous for the environment:	Dangerous for the environment:	Dangerous for the environment:
Yes	Yes	Yes	Yes
	Marine pollutant: Yes		
not restricted according ADR Speci	al Provision SP375, IATA-DGR Spec	ial Provision A197 and IMDG-Code 2	.10.2.7
14.6. Special precautions for	user		
Overland transport			
Classification code (ADR)	M7		
Special provisions (ADR)	274, 335, 375, 6	601	
Limited quantities (ADR)	5kg		

Sity
P002, IBC08, LP02, R001
MP10
3
90 3077
-
274, 335, 966, 967, 969
5 kg
LP02, P002
F-A
S-F
A
SW23
956
400kg
956
A97, A158, A179, A197, A215

Rail transport

Special provisions (RID)

274, 335, 375, 601

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.7. Transport in bulk according to	Annex II of Marpol and the IBC Code	
Limited quantities (RID) Packing instructions (RID)	5kg P002, IBC08, LP02, R001	

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

dibenzoyl peroxide	CAS-No. 94-36-0	1 - 15%
Quartz (SiO2)	CAS-No. 14808-60-7	40 - 60%

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

	dibenzoyl peroxide	CAS-No. 94-36-0	1 - 15%
--	--------------------	-----------------	---------

15.2. International regulations

CANADA

dibenzoyl peroxide (94-36-0)
Listed on the Canadian DSL (Domestic Substances List)
Quartar (SiQ2) (14808 60 7)

Listed on the Canadian DSL	(Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Quartz (SiO2) (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date

01/21/2022

Full text of H-statements:

H241	Heating may cause a fire or explosion.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H350	May cause cancer.	

Abbreviations and acronyms:

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC50	Median effective concentration	
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	
vPvB	Very Persistent and Very Bioaccumulative	
A health hazard	1 - Materials that, under emergency conditions, can cause significant irritation.	
PA fire hazard	1 - Materials that must be preheated before ignition can occur.	
PA reactivity	0 - Material that in themselves are normally stable, even under fire conditions.	
ard Rating	\sim	
llth	1 Slight Hazard - Irritation or minor reversible injury possible	
nmability	1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)	
sical	0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NC react with water, polymerize, decompose, condense, or self-react. Non-Explosives.	

Indication of changes:

Section	Changed item	Change	Comments
14	Transport information	Modified	

SDS_US_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.



according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 01/25/2022 Revision date: 01/25/2022 Supersedes: 08/10/2017 Versi

SECTION 1: Identification	
1.1. Identification	
Product form	Mixture
Product name	HIT-1, A
Product code	BU Anchor
1.2. Recommended use and restricti	ons on use
Use of the substance/mixture	Composite mortar component for fasteners in the construction industry
Recommended use	For professional use only
1.3. Supplier	
Supplier Hilti, Inc. Legacy Tower, Suite 1000 7250 Dallas Parkway Plano, TX 75024 - USA T +1 9724035800 1-800-879-8000 toll free - F +1 918 254 0522	Department issuing data specification sheet Hilti Entwicklungsgesellschaft mbH Hiltistraße 6 Kaufering, 86916 - Deutschland T +49 8191 906876 anchor.hse@hilti.com
1.4. Emergency telephone number	
Emergency number	Chem-Trec Tel.: 1 800 424 9300 (USA, PR, Virgin Islands, Canada) Tel.: 703 527 3887 (Other countries) +1 918 8723000 1-800-879-8000 toll free

Version: 1.1

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Serious eye damage/eye irritation, Category 2 Skin sensitisation, Category 1 Full text of H-statements: see section 16 H319 H317

Causes serious eye irritation. May cause an allergic skin reaction.

Tuit lext of TP-statements. See Section To


2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US)

Signal word (GHS US) Hazard statements (GHS US)

Precautionary statements (GHS US)



P262 - Do not get in eyes, on skin, or on clothing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P302+P352 If on skin: Wash with plenty of water.

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2 Mixtures

Name	Product identifier	%	GHS-US classification
Quartz (SiO2)	(CAS-No.) 14808-60-7	40 - 60	Carc. 1A, H350
2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester	(CAS-No.) 2082-81-7	10 – 25	Skin Sens. 1B, H317
vinyltoluene	(CAS-No.) 25013-15-4	5 – 8	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319
ethylenedimethacrylate, stabilized	(CAS-No.) 97-90-5	1 – 5	Skin Sens. 1, H317 STOT SE 3, H335
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol	(CAS-No.) 27813-02-1	1 – 5	Eye Irrit. 2A, H319 Skin Sens. 1, H317
1,1'-(p-tolylimino)dipropan-2-ol	(CAS-No.) 38668-48-3	< 1	Acute Tox. 2 (Oral), H300 Eye Irrit. 2A, H319

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures	
First-aid measures general	Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	Wash contaminated clothing before reuse. Wash with plenty of water/ If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.
4.2. Most important symptoms and eff	ects (acute and delayed)
Potential adverse human health effects and symptoms	No additional information available.
Symptoms/effects after skin contact	May cause an allergic skin reaction.
Symptoms/effects after eye contact	May cause severe irritation.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media

Water spray. Carbon dioxide. Dry powder. Foam. Sand.

HIT-1, A

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Unsuitable extinguishing media	Do not use a heavy water stream.
5.2. Specific hazards arising from th	e chemical
lazardous decomposition products in case of re	Thermal decomposition generates : Carbon dioxide. Carbon monoxide.
5.3. Special protective equipment ar	nd precautions for fire-fighters
irefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment including respiratory protection.
SECTION 6: Accidental release m	neasures
6.1. Personal precautions, protective	e equipment and emergency procedures
General measures	Spilled material may present a slipping hazard.
5.1.1. For non-emergency personnel	
mergency procedures	Evacuate unnecessary personnel.
.1.2. For emergency responders	
Protective equipment	Use personal protective equipment as required. Equip cleanup crew with proper protection.
Emergency procedures	Ventilate area.
5.2. Environmental precautions	
Prevent entry to sewers and public waters. Notify	authorities if liquid enters sewers or public waters.
3.3. Methods and material for contai	nment and cleaning up
or containment	Collect spillage.
lethods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. Store away from other materials.
Other information	Dispose of materials or solid residues at an authorized site.
6.4. Reference to other sections	
or further information refer to section 8: "Exposi-	ure controls/personal protection". For further information refer to section 13.
SECTION 7: Handling and storage	e
7.1. Precautions for safe handling	
Precautions for safe handling	Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.

Hygiene measures

Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and oth exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash

7.2. Conditions for safe storage, inclu	iding any incompatibilities
Storage conditions	Keep cool. Protect from sunlight.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Storage temperature	5 – 25 °C
Heat and ignition sources	Keep away from heat and direct sunlight.

contaminated clothing before reuse.

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

o. i. Control parameters		
HIT-1, A		
USA - ACGIH - Occupational Exposure Lim	its	
Local name	Vinyltoluene	
ACGIH OEL TWA [ppm]	50 ppm	
ACGIH OEL STEL [ppm]	100 ppm	
Remark (ACGIH)	TLV® Basis: URT & eye irr. Notations: A4 (Not classifiable as a Human Carcinogen)	
Regulatory reference	ACGIH 2021	
USA - OSHA - Occupational Exposure Limit	'S	
Local name	Vinyl toluene	
OSHA PEL TWA [1]	480 mg/m³	
OSHA PEL TWA [2]	100 ppm	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	
2-Propenoic acid, 2-methyl-, 1,4-butanediyl	ester (2082-81-7)	
No additional information available		
vinyltoluene (25013-15-4)		
USA - ACGIH - Occupational Exposure Lim	its	
Local name	Vinyl toluene	
ACGIH OEL TWA [ppm]	50 ppm	
ACGIH OEL STEL [ppm]	100 ppm	
Remark (ACGIH)	URT & eye irr	
USA - OSHA - Occupational Exposure Limit	is is a second s	
Local name	Vinyl toluene	
OSHA PEL TWA [1]	480 mg/m ³	
OSHA PEL TWA [2]	100 ppm	
ethylenedimethacrylate, stabilized (97-90-5)		
No additional information available		
2-Propenoic acid, 2-methyl-, monoester wit	h 1,2-propanediol (27813-02-1)	
No additional information available		
1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3		
No additional information available		
Quartz (SiO2) (14808-60-7)		
USA - ACGIH - Occupational Exposure Lim	its	
Local name	Silica crystaline - quartz	
ACGIH OEL TWA	0.025 mg/m ³ (Respirable fraction)	
Remark (ACGIH)	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)	
Regulatory reference	ACGIH 2022	
USA - OSHA - Occupational Exposure Limit	is	
Local name	Silica, crystalline quartz, respirable dust	

Additional information

The product has a pasty consistency. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Appropriate engineering controls

Appropriate engineering controls Environmental exposure controls Ensure adequate ventilation. Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Safety glasses. Gloves. Protective clothing. Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Туре	Material	Permeation	Thickness (mm)	Penetration
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	> 0,4	

Eye protection:

Wear security glasses which protect from splashes

Туре	Field of application	Characteristics
Safety glasses	Droplet	clear

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of inadequate ventilation wear respiratory protection.

Device	Filter type	Condition
Disposable half mask	Filter A1/B1	Vapour protection

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and	l chemical properties
Physical state	Solid
Appearance	Thixotropic paste.
Colour	Beige
Odour	strong unpleasant odour
Odour threshold	No data available
pН	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	No data available
Flash point	No data available
Relative evaporation rate (butylacetate=1)	No data available
Flammability (solid, gas)	No data available
Vapour pressure	No data available
Relative vapour density at 20 °C	No data available
Relative density	No data available
Density	1.72 g/cm³
Solubility	insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	No data available

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Auto-ignition temperature	No data available
Decomposition temperature	No data available
Viscosity, kinematic	No data available
Viscosity, dynamic	No data available
Explosive limits	No data available
Explosive properties	No data available
Oxidising properties	No data available

9.2. Other information

2.8 % (DIN EN ISO 11890-2)

SECTION 10: Stability and reactivity

10.1. Reactivity

VOC content

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effe	cts		
Acute toxicity (oral)	Not classified		
Acute toxicity (dermal)	Not classified		
Acute toxicity (inhalation)	Not classified		
2-Propenoic acid, 2-methyl-, 1,4-butanediyl es	ster (2082-81-7)		
LD50 oral rat	10066 mg/kg		
LD50 dermal rat	> 3000 mg/kg		
vinyltoluene (25013-15-4)			
LD50 oral rat	3375 mg/kg bodyweight (Rat, Male, Experimental value, Oral, 14 day(s))		
LD50 dermal rabbit	> 4585 mg/kg bodyweight (24 h, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))		
LC50 Inhalation - Rat	> 16.891 mg/l (4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))		
ethylenedimethacrylate, stabilized (97-90-5)			
LD50 oral rat	8700 mg/kg (Rat, Male / female, Experimental value, Oral, 14 day(s))		
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))		
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)			
LD50 oral rat	> 5000 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; >=2000 mg/kg bodyweight; Rat; Experimental value)		
LD50 dermal rabbit	≥ 5000 mg/kg bodyweight (Rabbit; Experimental value)		
1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)			
LD50 oral rat	25 mg/kg		

HIT-1, A

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)	
LD50 dermal rat	> 2000 mg/kg
Skin corrosion/irritation	Not classified
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Quartz (SiO2) (14808-60-7)	
IARC group	1 - Carcinogenic to humans
Reproductive toxicity	Not classified
STOT-single exposure	Not classified
ethylenedimethacrylate, stabilized (97-90-5)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified
Viscosity, kinematic	
Potential adverse human health effects and symptoms	No additional information available.
Symptoms/effects after skin contact	May cause an allergic skin reaction.
Symptoms/effects after eye contact	May cause severe irritation.

SECTION 12: Ecological information

12.1. Toxicity

2-Propenoic acid, 2-methyl-, 1,4-butanediy	ester (2082-81-7)	
LC50 - Other aquatic organisms [1]	9.79 mg/l	
NOEC (acute)	7.51 mg/l	
NOEC (chronic)	20 mg/l	
vinyltoluene (25013-15-4)		
ErC50 algae	4.3 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value)	
NOEC (acute)	5.2 mg/kg	
NOEC (chronic)	1.636 mg/l	
ethylenedimethacrylate, stabilized (97-90-5)	
LC50 - Fish [1]	15.95 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Static system, Experimental value, GLP)	
EC50 - Crustacea [1]	44.9 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Experimental value, GLP)	
ErC50 algae	19 mg/l (OECD 201: Alga, Growth Inhibition Test, 96 h, Pseudokirchneriella subcapitata, Static system, Experimental value, GLP)	
2-Propenoic acid, 2-methyl-, monoester with	th 1,2-propanediol (27813-02-1)	
LC50 - Fish [1]	493 mg/l (48 h; Leuciscus idus; GLP)	
EC50 - Crustacea [1]	> 143 mg/l (48 h; Daphnia magna; GLP)	
ErC50 algae	97.2 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)	

HIT-1, A

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)		
Threshold limit - Algae [1]	> 97.2 mg/l (72 h; Pseudokirchneriella subcapitata; GLP)	
Threshold limit - Algae [2]	> 97.2 mg/l (72 h; Pseudokirchneriella subcapitata; GLP)	
1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)		
LC50 - Fish [1]	≈ 17 mg/l	
LC50 - Other aquatic organisms [1]	245 mg/l	
EC50 - Crustacea [1]	28.8 mg/l	
NOEC (acute)	57.8 mg/l	

12.2. Persistence and degradability

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)			
Biodegradation	84 %		
vinyltoluene (25013-15-4)			
Persistence and degradability	Not readily biodegradable in water.		
Biochemical oxygen demand (BOD)	0 g O ₂ /g substance		
Chemical oxygen demand (COD)	2.88 g O ₂ /g substance		
ThOD	3.12 g O ₂ /g substance		
BOD (% of ThOD)	0		
ethylenedimethacrylate, stabilized (97-90-5)			
Persistence and degradability	Readily biodegradable in water.		
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)			
Persistence and degradability	Readily biodegradable in water.		
Quartz (SiO2) (14808-60-7)			
Persistence and degradability	Biodegradability: not applicable.		
Chemical oxygen demand (COD)	Not applicable (inorganic)		
ThOD	Not applicable (inorganic)		

12.3. Bioaccumulative potential

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)		
Partition coefficient n-octanol/water (Log Pow)	3.1	
vinyltoluene (25013-15-4)		
BCF - Fish [1]	120 – 170 (Other, 30 day(s), Lepomis macrochirus, Flow-through system, Fresh water, Experimental value)	
Partition coefficient n-octanol/water (Log Pow)	3.26 – 3.36 (Experimental value, 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	
ethylenedimethacrylate, stabilized (97-90-5)		
BCF - Other aquatic organisms [1]	2.96 (BCFBAF v3.00, QSAR)	
Partition coefficient n-octanol/water (Log Pow)	2.4 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
2-Propenoic acid, 2-methyl-, monoester with	1,2-propanediol (27813-02-1)	
BCF - Fish [1]	≤ 100	
BCF - Fish [2]	3.2 Quantitative structure-activity relationship (QSAR)	
Partition coefficient n-octanol/water (Log Pow)	0.97 (OECD 102 method)	
Bioaccumulative potential	Low bioaccumulation potential (BCF < 500).	
1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)		
Partition coefficient n-octanol/water (Log Kow)	2.1	
Quartz (SiO2) (14808-60-7)		
Bioaccumulative potential	No bioaccumulation data available.	

12.4. Mobility in soil

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

vinyltoluene (25013-15-4)		
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.985 (log Koc, SRC PCKOCWIN v2.0, QSAR)	
Ecology - soil	Low potential for adsorption in soil.	
ethylenedimethacrylate, stabilized (97-90-5)		
Surface tension	No data available (test not performed)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.367 – 2.12 (log Koc, SRC PCKOCWIN v2.0, QSAR)	
Ecology - soil	Highly mobile in soil.	
2-Propenoic acid, 2-methyl-, monoester w	ith 1,2-propanediol (27813-02-1)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.9 (log Koc, Calculated value)	
Ecology - soil	Highly mobile in soil.	
Quartz (SiO2) (14808-60-7)		
Surface tension	No data available in the literature	
Ecology - soil	Low potential for mobility in soil.	

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. **Disposal methods**

Regional legislation (waste) Disposal must be done according to official regulations. Product/Packaging disposal recommendations After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations. Avoid release to the environment.

Ecology - waste materials

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	ΙΑΤΑ	RID
14.1. UN number			
Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping nan	ne		
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)		
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.6. Special precautions for user

Overland transport Not regulated

Transport by sea

Not regulated

Air transport Not regulated

Rail transport

Not regulated

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester	CAS-No. 2082-81-7	10 – 25%
vinyltoluene	CAS-No. 25013-15-4	5-8%
ethylenedimethacrylate, stabilized	CAS-No. 97-90-5	1 – 5%
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol	CAS-No. 27813-02-1	1 – 5%
1,1'-(p-tolylimino)dipropan-2-ol	CAS-No. 38668-48-3	< 1%
Quartz (SiO2)	CAS-No. 14808-60-7	40 - 60%

15.2. International regulations

CANADA

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7) Listed on the Canadian DSL (Domestic Substances List)

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1) Listed on the Canadian DSL (Domestic Substances List)

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)

Listed on the Canadian DSL (Domestic Substances List)

Quartz (SiO2) (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Quartz (SiO2) (14808-60-7)			
Listed on IARC (International Agency for Research on Cancer)			

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

HIT-1, A

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Rev	sion date	01/25/2022					
Full	Full text of H-statements:						
	H226	Flammable liquid and vapour.					
	H300	Fatal if swallowed.					
	H315	Causes skin irritation.					
H317 May cause an		May cause an allergic skin reaction.					
	H319	Causes serious eye irritation.					
H332		Harmful if inhaled.					
H335 May cause respiratory irr		May cause respiratory irritation.					
	H350	May cause cancer.					

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways European Agreement concerning the International Carriage of Dangerous Goods by Road Acute Toxicity Estimate		
ADR			
ATE			
BCF	Bioconcentration factor		
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008		
DMEL	Derived Minimal Effect level		
DNEL	Derived-No Effect Level		
EC50	Median effective concentration		
IARC	International Agency for Research on Cancer		
IATA	International Air Transport Association		
IMDG	International Maritime Dangerous Goods		
LC50	Median lethal concentration		
LD50	Median lethal dose		
LOAEL	Lowest Observed Adverse Effect Level		
NOAEC	No-Observed Adverse Effect Concentration		
NOAEL	No-Observed Adverse Effect Level		
NOEC	No-Observed Effect Concentration		
OECD	Organisation for Economic Co-operation and Development		
PBT	Persistent Bioaccumulative Toxic		
PNEC	Predicted No-Effect Concentration		
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006		
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail		
SDS	Safety Data Sheet		
vPvB	Very Persistent and Very Bioaccumulative		
PA health hazard	1 - Materials that, under emergency conditions, can cause significant irritation.		
PA fire hazard	1 - Materials that must be preheated before ignition can occur.		
PA reactivity	0 - Material that in themselves are normally stable, even		

under fire conditions.



Indication of changes:						
Section	Changed item	Change	Comments			

3	Composition/information on	Modified	
	Ingredients		

SDS_US_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.