

SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2015/830

DGE01 (SINTO ST-PE) - Part A

Bi-component injection system for chemical anchor on construction materials
Mastic based polyester resin unsaturated

Revision n. **03**

Dated **24/02/2021**

Printed on **24/02/2021**

Page n. 1 / 13 part A

Replaced revision: 02

(Dated: 18/02/2016)



1 - Identification of the substance/mixture and of the company/undertaking

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Bi-component injection system for chemical anchor on construction materials.

1.3. Details of the supplier of the safety data sheet

Name	Tecfi S.p.A.
Full address	S.S.Appia km 193
District and Country	81050 Pastorano (CE) - Italia - tel. 0823 88 3338 - fax 0823 - 883260
e-mail (e-mail address of the competent person, responsible for the Safety Data Sheet)	rdc@tecfi.it

1.4. Emergency telephone number

For urgent inquiries refer to

Osp. NIGUARDA CA' GRANDA – Milano 02/66101029
CAV Policlinico "A. Gemelli" - Roma 06/3054343
Osp. "A. Cardarelli" - Napoli 081/7472870

2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Warning

SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2015/830

DGE01 (SINTO ST-PE) - Part A

Bi-component injection system for chemical anchor on construction materials
Mastic based polyester resin unsaturated

Revision n. **03**

Dated **24/02/2021**

Printed on **24/02/2021**

Page n. 2 / 13 part A

Replaced revision: 02

(Dated: 18/02/2016)



Hazard statements:

H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements:

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P280	Wear protective gloves / eye protection / face protection.
P302+P352	IF ON SKIN: wash with plenty of water / . . .
P333+P313	If skin irritation or rash occurs: Get medical advice / attention.
P502	Refer to manufacturer or supplier for information on recovery or recycling.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
2-Hydroxyethyl methacrylate CAS 868-77-9 EC 212-782-2 INDEX 607-124-00-X Reg. no. 01-2119490169-29	5 ≤ x < 11	Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317, Classification note according to Annex VI to the CLP Regulation: D
Vinyltoluene CAS 25013-15-4 EC 246-562-2 INDEX - Reg. no. 01-2119622074-50	5 ≤ x < 9	Flam. Liq. 3 H226, Acute Tox. 4 H332, Asp. Tox. 1 H304, Eye Irrit. 2 H319, Skin Irrit. 2 H315, Aquatic Acute 1 H400 M=1, Aquatic Chronic 2 H411

The full wording of hazard (H) phrases is given in section 16 of the sheet.

Quartz (SiO₂) - CAS 14808-60-7 - C%: >=50 - <80:

The quartz contained in the product is classified as non-hazardous. Furthermore, being linked to the other liquid / pasty components of the mixture, it is not freely available during use. The final product has a pasty consistency and the limits of exposure to inhalable dusts are not relevant.

SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2015/830

DGE01 (SINTO ST-PE) - Part A

Bi-component injection system for chemical anchor on construction materials
Mastic based polyester resin unsaturated

Revision n. **03**

Dated **24/02/2021**

Printed on **24/02/2021**

Page n. 3 / 13 part A

Replaced revision: 02

(Dated: 18/02/2016)



4. Description of first aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2015/830

DGE01 (SINTO ST-PE) - Part A

Bi-component injection system for chemical anchor on construction materials
Mastic based polyester resin unsaturated

Revision n. **03**

Dated **24/02/2021**

Printed on **24/02/2021**

Page n. 4 / 13 part A

Replaced revision: 02

(Dated: 18/02/2016)



6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

Store in a well ventilated place, storage range temperature between 5°C and 30°C. Keeping the containers closed when not used. Do not smoke while handling. Keep far away from sources of heat, naked flames and sparks and other sources of ignition. Make sure that equipment is available for cooling the vessels, to prevent the danger of overpressure and overheating in the event of fire in the vicinity.

7.3. Specific end use(s)

Information not available

SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2015/830

DGE01 (SINTO ST-PE) - Part A

Bi-component injection system for chemical anchor on construction materials
Mastic based polyester resin unsaturated

Revision n. **03**

Dated **24/02/2021**

Printed on **24/02/2021**

Page n. 5 / 13 part A

Replaced revision: 02

(Dated: 18/02/2016)



8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

TLV-ACGIH

ACGIH 2019

2-Hydroxyethyl methacrylate

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,482	mg/l
Normal value in marine water	0,482	mg/l
Normal value for fresh water sediment	3,79	mg/kg/d
Normal value for marine water sediment	3,79	mg/kg/d
Normal value for water, intermittent release	1	mg/l
Normal value of STP microorganisms	10	mg/l
Normal value for the terrestrial compartment	0,476	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,83 mg/kg bw/d				
Inhalation				2,9 mg/m3				4,9 mg/m3
Skin				0,83 mg/kg/d				1,3 mg/kg bw/d

Vinyltoluene

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
TLV-ACGIH			50		100

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

Quartz (SiO₂):

The quartz contained in the product is classified as non-hazardous. Furthermore, being linked to the other liquid / pasty components of the mixture, it is not freely available during use. The final product has a pasty consistency and the limits of exposure to inhalable dusts are not relevant.

SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2015/830

DGE01 (SINTO ST-PE) - Part A

Bi-component injection system for chemical anchor on construction materials
Mastic based polyester resin unsaturated

Revision n. **03**

Dated **24/02/2021**

Printed on **24/02/2021**

Page n. 6 / 13 part A

Replaced revision: 02
(Dated: 18/02/2016)



8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2015/830

DGE01 (SINTO ST-PE) - Part A

Bi-component injection system for chemical anchor on construction materials
Mastic based polyester resin unsaturated

Revision n. **03**

Dated **24/02/2021**

Printed on **24/02/2021**

Page n. 7 / 13 part A

Replaced revision: 02

(Dated: 18/02/2016)



9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	paste	Lower explosive limit	Not available
Colour	cream	Upper explosive limit	Not available
Odour	characteristic	Vapour pressure	Not available
Odour threshold	Not available	Vapour density	Not available
pH	Not available	Relative density	1,60 - 1,80 kg/l
Melting point / freezing point	Not available	Solubility	insoluble in water
Initial boiling point	Not available	Partition coefficient: n-octanol/water	Not available
Boiling range	Not available	Auto-ignition temperature	Not available
Flash point	Not available	Decomposition temperature	Not available
Evaporation Rate	Not available	Viscosity	Not available
Flammability of solids and gases	Not available	Explosive properties	Not available
Lower inflammability limit	Not available	Oxidising properties	Not available
Upper inflammability limit	Not available		

9.2. Other information

Information not available

10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.
To avoid the exposure on the sunlight.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2015/830

DGE01 (SINTO ST-PE) - Part A

Bi-component injection system for chemical anchor on construction materials
Mastic based polyester resin unsaturated

Revision n. **03**

Dated **24/02/2021**

Printed on **24/02/2021**

Page n. 8 / 13 part A

Replaced revision: 02

(Dated: 18/02/2016)



11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.
It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:	> 20 mg/l
LD50 (Oral) of the mixture:	Not classified (no significant component)
LD50 (Dermal) of the mixture:	Not classified (no significant component)

2-Hydroxyethyl methacrylate

LD50 (Oral):	5564 mg/kg RAT
LD50 (Dermal):	> 5000 mg/kg RBT

Vinyltoluene

LD50 (Oral):	3680 mg/kg RAT
LD50 (Dermal):	> 4990 mg/kg RBT
LC50 (Inhalation):	3535 ppm/4h RAT

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2015/830

DGE01 (SINTO ST-PE) - Part A

Bi-component injection system for chemical anchor on construction materials
Mastic based polyester resin unsaturated

Revision n. **03**

Dated **24/02/2021**

Printed on **24/02/2021**

Page n. 9 / 13 part A

Replaced revision: 02

(Dated: 18/02/2016)



STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

2-Hydroxyethyl methacrylate

LC50 - for Fish	> 100 mg/l/96h (OECD TG 203)
EC50 - for Crustacea	> 380 mg/l/48h
EC50 - for Algae / Aquatic Plants	836 mg/l/72h
Chronic NOEC for Fish	< 100 mg/l (OECD TG 211)
Chronic NOEC for Crustacea	24,1 mg/l
Chronic NOEC for Algae / Aquatic Plants	400 mg/l 72 h

Vinyltoluene

LC50 - for Fish	5,2 mg/l/96h
EC50 - for Crustacea	9,3 mg/l/48h
EC50 - for Algae / Aquatic Plants	0,319 mg/l/72h
EC10 for Algae / Aquatic Plants	0,25 mg/l/72h

12.2. Persistence and degradability

2-Hydroxyethyl methacrylate

Rapidly degradable

Readily biodegradable in water.

Vinyltoluene

NOT rapidly degradable

12.3. Bioaccumulative potential

2-Hydroxyethyl methacrylate

Partition coefficient: n-octanol/water 0,42 Log Kow

Vinyltoluene

Partition coefficient: n-octanol/water 3,44 Log Kow

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2015/830

DGE01 (SINTO ST-PE) - Part A

Bi-component injection system for chemical anchor on construction materials
Mastic based polyester resin unsaturated

Revision n. **03**

Dated **24/02/2021**

Printed on **24/02/2021**

Page n. 10 / 13 part A

Replaced revision: 02

(Dated: 18/02/2016)



13. Disposal considerations

Non-hardened material (such as expired or damaged products and/or rejects): e.g.

08 04 09* Glue and sealing materials waste containing organic solvents or other dangerous substances

Hardened material, e.g.:

08 04 10 Glue and sealing materials waste or other dangerous substances, other than classified under 08 04 09.

Contaminated packaging

Untaminated packaging may be taken for recycling.

Packaging that cannot be cleaned should be disposed of as for product.

15 01 10* Packaging containing residues of or contaminated by dangerous substances

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2015/830

DGE01 (SINTO ST-PE) - Part A

Bi-component injection system for chemical anchor on construction materials
Mastic based polyester resin unsaturated

Revision n. **03**

Dated **24/02/2021**

Printed on **24/02/2021**

Page n. 11 / 13 part A

Replaced revision: 02

(Dated: 18/02/2016)



15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product	
Point	3

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3	Flammable liquid, category 3
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1	Skin sensitization, category 1
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H226	Flammable liquid and vapour.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2015/830

DGE01 (SINTO ST-PE) - Part A

Bi-component injection system for chemical anchor on construction materials
Mastic based polyester resin unsaturated

Revision n. **03**

Dated **24/02/2021**

Printed on **24/02/2021**

Page n. 12 / 13 part A

Replaced revision: 02

(Dated: 18/02/2016)



LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2015/830

DGE01 (SINTO ST-PE) - Part A

Bi-component injection system for chemical anchor on construction materials
Mastic based polyester resin unsaturated

Revision n. **03**

Dated **24/02/2021**

Printed on **24/02/2021**

Page n. 13 / 13 part A

Replaced revision: 02

(Dated: 18/02/2016)



GENERAL BIBLIOGRAPHY:

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

03.

SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2015/830

DGE01 (SINTO ST-PE) - Part B

Bi-component injection system for chemical anchor on construction materials
Mastic based polyester resin unsaturated

Revision n. **02**

Dated **26/02/2021**

Printed on **26/02/2021**

Page n. 1 / 13 part B

Replaced revision: 01

(Dated: 02/01/2020)



1 - Identification of the substance/mixture and of the company/undertaking

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use	Bi-component injection system for chemical anchor on construction materials
--------------	---

1.3. Details of the supplier of the safety data sheet

Name	Tecfi S.p.A.
Full Address	S.S.Appia km 193
District and Country	81050 Pastorano (CE) - Italia - tel. 0823 88 3338 - fax 0823 - 883260
e-mail (of the competent person responsible for the Safety Data Sheet)	rdc@tecfi.it

1.4. Emergency telephone number

For urgent inquiries refer to

Osp. NIGUARDA CA' GRANDA – Milano 02/66101029
CAV Policlinico "A. Gemelli" - Roma 06/3054343
Osp. "A. Cardarelli" - Napoli 081/7472870

2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication

Eye irritation, category 2	H319	Causes serious eye irritation.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.



Signal words: Warning

SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2015/830

DGE01 (SINTO ST-PE) - Part B

Bi-component injection system for chemical anchor on construction materials
Mastic based polyester resin unsaturated

Revision n. **02**

Dated **26/02/2021**

Printed on **26/02/2021**

Page n. 2 / 13 part B

Replaced revision: 01

(Dated: 02/01/2020)



Hazard statements:

H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.

Precautionary statements:

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P280	Wear protective gloves / eye protection / face protection.
P302+P352	IF ON SKIN: wash with plenty of water / . . .
P333+P313	If skin irritation or rash occurs: Get medical advice / attention.
P501	Dispose of contents/container in accordance with national regulations.
Contains:	Dibenzoyl peroxide

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

3. Composition/information on ingredients

3.2. Mixtures

Contains

Identification	x=Conc. %	Classification 1272/2008 (CLP)
Dibenzoyl peroxide CAS 94-36-0 EC 202-327-6 INDEX 617-008-00-0 Reg. no. 01-2119511472-50	11 ≤ x < 17	Org. Perox B H241, Eye Irrit. 2 H319, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=10, Aquatic Chronic 1 H410 M=10

The full wording of hazard (H) phrases is given in section 16 of the sheet.

Quartz (SiO₂) - CAS 14808-60-7 - C%: ≥50 - <80:

The quartz contained in the product is classified as non-hazardous. Furthermore, being linked to the other liquid / pasty components of the mixture, it is not The quartz contained in the product is classified as non-hazardous. Furthermore, being linked to the other liquid / pasty components of the mixture, it is not freely available during use. The final product has a pasty consistency and the limits of exposure to inhalable dusts are not relevant.

SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2015/830

DGE01 (SINTO ST-PE) - Part B

Bi-component injection system for chemical anchor on construction materials
Mastic based polyester resin unsaturated

Revision n. **02**

Dated **26/02/2021**

Printed on **26/02/2021**

Page n. 3 / 13 part B

Replaced revision: 01

(Dated: 02/01/2020)



4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2015/830

DGE01 (SINTO ST-PE) - Part B

Bi-component injection system for chemical anchor on construction materials
Mastic based polyester resin unsaturated

Revision n. **02**

Dated **26/02/2021**

Printed on **26/02/2021**

Page n. 4 / 13 part B

Replaced revision: 01
(Dated: 02/01/2020)



6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage

7.1. Precautions for safe handling

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

Store in a well ventilated place, storage range temperature between 5°C and 30°C. Keeping the containers closed when not used. Do not smoke while handling. Keep far away from sources of heat, naked flames and sparks and other sources of ignition. Make sure that equipment is available for cooling the vessels, to prevent the danger of overpressure and overheating in the event of fire in the vicinity.

7.3. Specific end use(s)

Information not available

SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2015/830

DGE01 (SINTO ST-PE) - Part B

Bi-component injection system for chemical anchor on construction materials
Mastic based polyester resin unsaturated

Revision n. **02**

Dated **26/02/2021**

Printed on **26/02/2021**

Page n. 5 / 13 part B

Replaced revision: 01

(Dated: 02/01/2020)



8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

TLV-ACGIH ACGIH 2019

Dibenzoyl peroxide

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
TLV-ACGIH		5			

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,00002	mg/l
Normal value in marine water	0,000002	mg/l
Normal value for fresh water sediment	0,0127	mg/kg/d
Normal value for marine water sediment	0,00127	mg/kg/d
Normal value for water, intermittent release	0,000602	mg/l
Normal value of STP microorganisms	0,35	mg/l
Normal value for the terrestrial compartment	0,0025	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on consumers			
	Acute local	Acute system- mic	Chronic local	Acute local	Acute system- mic	Chronic local	Chronic system- mic
Oral							2 mg/kg bw/d
Inhalation							39 mg/m3
Skin							13,3 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

Quartz (SiO₂):

The quartz contained in the product is classified as non-hazardous. Furthermore, being linked to the other liquid / pasty components of the mixture, it is not freely available during use. The final product has a pasty consistency and the limits of exposure to inhalable dusts are not relevant.

SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2015/830

DGE01 (SINTO ST-PE) - Part B

Bi-component injection system for chemical anchor on construction materials
Mastic based polyester resin unsaturated

Revision n. **02**

Dated **26/02/2021**

Printed on **26/02/2021**

Page n. 6 / 13 part B

Replaced revision: 01
(Dated: 02/01/2020)



8.2 Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways

SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2015/830

DGE01 (SINTO ST-PE) - Part B

Bi-component injection system for chemical anchor on construction materials
Mastic based polyester resin unsaturated

Revision n. **02**

Dated **26/02/2021**

Printed on **26/02/2021**

Page n. 7 / 13 part B

Replaced revision: 01

(Dated: 02/01/2020)



9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	paste
Colour	black
Odour	characteristic
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	Not available
Evaporation Rate	Not available
Flammability of solids and gases	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available

Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	1,50 - 1,70 kg/l
Solubility	Not available
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	Not available
Oxidising properties	Not available

9.2. Other information

active oxygen (%) < 1

10. Stability and reactivity

10.1. Reactivity

Information not available

10.2. Chemical stability

The product is stable if stored in original containers at temperatures lower than the self accelerated decomposition temperature (SADT). To avoid the exposure on the sunlight.

10.3. Possibility of hazardous reactions

Information not available

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition. Avoid transferring into containers that may have been contaminated with other substances. Avoid storing close to inflammable or combustible products.

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material

10.6. Hazardous decomposition products

Thermal decomposition can lead to the formation of explosive peroxides or other potentially hazardous substances

SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2015/830

DGE01 (SINTO ST-PE) - Part B

Bi-component injection system for chemical anchor on construction materials
Mastic based polyester resin unsaturated

Revision n. 02

Dated 26/02/2021

Printed on 26/02/2021

Page n. 8 / 13 part B

Replaced revision: 01
(Dated: 02/01/2020)



11. Toxicological information

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

Not classified (no significant component)

LD50 (Oral) of the mixture:

Not classified (no significant component)

LD50 (Dermal) of the mixture:

Not classified (no significant component)

Dibenzoyl peroxide

LD50 (Oral) > 2000 mg/kg RAT

LC50 (Inhalation) > 24,3 mg/l/4h RAT

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2015/830

DGE01 (SINTO ST-PE) - Part B

Bi-component injection system for chemical anchor on construction materials
Mastic based polyester resin unsaturated

Revision n. **02**

Dated **26/02/2021**

Printed on **26/02/2021**

Page n. 9 / 13 part B

Replaced revision: 01

(Dated: 02/01/2020)



12. Ecological information

12.1. Toxicity

Dibenzoyl peroxide

LC50 - for Fish	> 0,0602 mg/l/96h (OECD TG 203)
EC50 - for Crustacea	> 0,11 mg/l/48h (OECD TG 202)
EC50 - for Algae / Aquatic Plants	> 0,0711 mg/l/72h (OECD TG 201)
EC10 for Crustacea	> 0,001 mg/l/28d (OECD TG 211)
Chronic NOEC for Fish	> 0,0316 mg/l 96 h
Chronic NOEC for Algae / Aquatic Plants	> 0,02 mg/l 72 h

mixture/product

LC50 - Fish	> 100 mg/l/96h fish (OECD TG 203)
EC50 - Crustaceans	> 100 mg/l/48h daphia magna (OECD TG 202)
EC50 - Algae / Aquatic Plants	> 100 mg/l/72h algae – Pseudokirchneriella subcapitata (OECD TG 201 Acuta e Cronica)
NOEC - Chronic Fish	> 100 mg/l/28 d fish, Juvenile Growth Test (OECD TG 215)

12.2. Persistence and degradability

Dibenzoyl peroxide
Rapidly degradable
71% in water 28 d (OECD TG 301 D)

12.3. Bioaccumulative potential

Dibenzoyl peroxide
Partition coefficient: n-octanol/water 3,2 Log Kow (OECD TG 117)

12.4. Mobility in soil

Dibenzoyl peroxide
Partition coefficient: soil/water 3,8 (OECD TG 121)

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2015/830

DGE01 (SINTO ST-PE) - Part B

Bi-component injection system for chemical anchor on construction materials
Mastic based polyester resin unsaturated

Revision n. **02**

Dated **26/02/2021**

Printed on **26/02/2021**

Page n. 10 / 13 part B

Replaced revision: 01
(Dated: 02/01/2020)



13. Disposal considerations

Non-hardened material (such as expired or damaged products and/or rejects): e.g.

08 04 09* Glue and sealing materials waste containing organic solvents or other dangerous substances

Hardened material, e.g.:

08 04 10 Glue and sealing materials waste or other dangerous substances, other than classified under 08 04 09.

Contaminated packaging

Untampered packaging may be taken for recycling.

Packaging that cannot be cleaned should be disposed of as for product.

15 01 10* Packaging containing residues of or contaminated by dangerous substances

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations

14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Informazione non pertinente

SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2015/830

DGE01 (SINTO ST-PE) - Part B

Bi-component injection system for chemical anchor on construction materials
Mastic based polyester resin unsaturated

Revision n. **02**

Dated **26/02/2021**

Printed on **26/02/2021**

Page n. 11 / 13 part B

Replaced revision: 01

(Dated: 02/01/2020)



15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected

No chemical safety assessment has been processed for the mixture and the substances it contains.

15.2. Valutazione della sicurezza chimica

Non è stata elaborata una valutazione di sicurezza chimica per la miscela e le sostanze in essa contenute.

16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Org. Perox B	Organic peroxide, category B
Eye Irrit. 2	Eye irritation, category 2
Skin Sens. 1	Skin sensitization, category 1
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
H241	Heating may cause a fire or explosion.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2015/830

DGE01 (SINTO ST-PE) - Part B

Bi-component injection system for chemical anchor on construction materials
Mastic based polyester resin unsaturated

Revision n. **02**

Dated **26/02/2021**

Printed on **26/02/2021**

Page n. 12 / 13 part B

Replaced revision: 01

(Dated: 02/01/2020)



LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2015/830

DGE01 (SINTO ST-PE) - Part B

Bi-component injection system for chemical anchor on construction materials
Mastic based polyester resin unsaturated

Revision n. **02**

Dated **26/02/2021**

Printed on **26/02/2021**

Page n. 13 / 13 part B

Replaced revision: 01

(Dated: 02/01/2020)



LEGEND:

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

08.