

**Included in delivery**

- 1 Pipe flashing
- 1 cartridge of EJOPLAST joint sealant
- 1 EJOT® self-drilling screw set

Dektite® Soaker**Installation Kit**

For pipe Ø [mm]	Base [mm]	Roof pitch [°]	Cartridge capacity [ml]	Screws [pcs.]	PU	Price/1 [EUR]	Order description	Article number
75 - 155	410 x 360	0 - 60	80	30	1		DF 602	8 206 024 704
114 - 254	485 x 460	0 - 60	80	36	1		DF 603	8 206 034 704
254 - 406	708 x 635	0 - 60	310	52	1		DF 605	8 206 054 704
380 - 610	1006 x 905	0 - 60	310	96	1		DF 606	8 206 064 704

Application Range

- For waterproofing pipes with large openings

Note

Do not use on smooth surfaces.

Advantages:


- Large base ensures optimum positioning
- Reliable and easy installation
- Seals pipe and roof in a single work step
- Prevents rainwater back-up



1. Adjust Dektite® to the pipe.



2. Adjust Dektite® to the profiled sheet and mark.



3. Mark the outline of the Dektite® on the roof then remove it and mark a 30 mm overlap area.




4. Cut out the roof inside of the marked 30 mm area. Trim sharp edges. Timber supports may be installed to support the roof where ribs have been removed.



5. Apply sealant and fit Dektite® accurately to the profiled sheet.



6. Fix to the middle front and middle back of the Dektite® and fix progressively towards the edge.



7. Use provided metal strips to seal overlapping ends. Trim excess sides

Поставщик продукции ООО "1001 КРЕПЕЖ" www.1001krep.ru +7 (495) 230-10-82